


Facts

- Product pre-wired and fully assembled
- 3.3A 120V AC power supply required
- Shipping weight approximately 6-1/2 lbs. [3 kg]
- Shipping dimensions
11-1/2" x 11-1/2" x 9" [292.1 x 292.1 x 228.4 mm]



Create the perfect mood lighting with Tentnology's® customized dimmer switches.

Parts

- Cast aluminum white enamel finished outdoor lamp holder
- Adjustable light housing
- Nylon bell mount, strain relief
- 4 lockit loops, 1 beaded tie
- 25' [7.62m] white power cord – #18/3SJT
- Molded 3-prong male plug
- Mounting with 1/4-20 thumbscrew (to any position on a 2" Marquee center pole)
- 4-100W globe lights, G40 White

Note

This product is internationally compatible, but must be modified to suit local voltage standards for proper use. Please contact Tentnology's® office for configuration details.

The use of Grounds Fault Interrupters are strongly recommended when installing electrical equipment in any tenting application.

SYSTEM STATISTICS

GLOBE	Suggested Use	Description	Light Output Lumens	Amps	Watts
Standard	1 per tent, up to 400 sq.ft. [37.21 sq.m] for social lighting	4 x 100W bulbs G40	6,000	3.3	400
High Output	as per above	4 x 150W bulbs	9,000	5	600

Tentnology® Co.
15427-66th Avenue
Surrey, British Columbia
Canada V3S 2A1

Tel: 604 597-8368
Fax: 604 597-8749
Toll Free (Canada & USA):
1-800-663-8858
Email: tent@tentnology.com
Web Site: www.tentnology.com

